














DATA SHEET
FICHA TECNICA

CODIGO PK
PKMD1560DN1

NAME OF SERIES OR ITEM NUMBER	6P061M
LAST UPDATE	June 2016

TECHNICAL CHARACTERISTICS CARACTERISTICAS TECNICAS		PORCELAMIKA VALUES / VALORES	NORMA ISO 13006 REQUISITOS / REQUIREMENTS PAVIMENTOS	TEST METHOD AS PER IOS NORM TEST DE ACUERDO A
	LENGTH AND WIDTH DIMENSIONES (MM)	-0.03 0~+0.23	±0.5%	UNI EN ISO 10545-2
	STRAIGHTNESS OF SIDE RECTITUD LATERAL (MM)	-0.05~+0.07	±0.5%	UNI EN ISO 10545-2
	RECTANGULAR SQUARENESS ORTOGONALIDAD (MM)	-0.07~+0.06	±0.6%	UNI EN ISO 10545-2
	SURFACE FLATNESS PLANARIDAD (MM)	Center Curvature : -0.05~+0.03 Warpage : -0.03~+0.04 Edge Curvature : -0.05~+0.07	±0.5%	UNI EN ISO 10545-2
	THICKNESS (MM) ESPESOR	10.1~10.2		UNI EN ISO 10545-2
	WATER ABSORPTION ABSORCION DE AGUA	7.1E	$E \leq 0.50 \%$	UNI EN ISO 10545-3
	BENDING RESISTANCE RESISTENCIA A LA FLEXION	27 MPA	$\geq 35\text{Mpa}$	UNI EN ISO 10545-4
	BREAKING STRENGTH FUERZA DE ROTURA	1494N	$\geq 1300\text{N}$	UNI EN ISO 10545-4
	CHEMICAL RESISTANCE RESISTENCIA A PRODUCTOS QUIMICOS	GB	GB Para Esmaltados UB para Pulidos	UNI EN ISO 10545-14
	STAIN RESISTANCE RESISTENCIA A LA MANCHAS	5	$\geq \text{Grado } 3$	UNI EN ISO 10545-14
	ABRASION RESISTANCE (PEI) RESISTENCIA A LA ABRASION SUPERFICIAL (PEI)	3	Max. 175 mm ³	UNI EN ISO 10545-7
	MOHS HARDNESS DUREZA SUPERFICIAL (ESCALA MOHS)	7	MOHS 1-10	UNI EN ISO 10545-7
	SHADE VARIATION CLASS VARIACION DE TONALIDAD	V2	V1-V4	DIN 51094

PACKING INFORMATION
INFORMACION DE EMPAQUES

SIZE FORMATO	M2/BOX M2/CNT	PCS./BOX PZA./CAJA	BOX/PALLET CAJA/PALETA	M2/PALLET M2/PALETA	KG/BOX KG/CAJA	KG/PALLET KG/PALETA
150x600mm	0.99	11	72	71.28	20.5	30