














DATA SHEET
FICHA TECNICA

Codigo Pk	
PKSP4040RV1	Graniti Beige
PKSP4040RV2	Light grey
PKSP4040RV3	Antracita
PKSP4040RV4	Grey

NAME OF SERIES OR ITEM NUMBER:	Serie Graniti 40 x 40 cm
LAST UPDATE	DIC. 2016

TECHNICAL CHARACTERISTICS CARACTERISTICAS TECNICAS		PORCELAMIKA VALUES / VALORES	NORMA ISO 13006 REQUISITOS / REQUIREMENTS PAVIMENTOS	TEST METHOD AS PER IOS NORM TEST DE ACUERDO A
	LENGTH AND WIDTH DIMENSIONES (MM)	± (+0.1 + 0.7) %	± 0.6 %	UNI EN ISO 10545-2
	STRAIGHTNESS OF SIDE RECTITUD LATERAL (MM)	± (-0.06 + 0.04) %	± 0.5%	UNI EN ISO 10545-2
	RECTANGULAR SQUARENESS ORTOGONALIDAD (MM)	± (-0.06 + 0.04) %	± 0.6%	UNI EN ISO 10545-2
	SURFACE FLATNESS PLANARIDAD (MM)	± (-0.06 + 0.05) %	± 0.5%	UNI EN ISO 10545-2
	THICKNESS ESPESOR (MM)	± (7.9~ 8.2)%	± 5 %	UNI EN ISO 10545-2
	WATER ABSORPTION ABSORCION DE AGUA	≤ 0.05%	≤ 0.5%	UNI EN ISO 10545-3
	BENDING RESISTANCE RESISTENCIA A LA FLEXION	≥ 45.2 MPA	≥ 35 MPA	UNI EN ISO 10545-4
	BREAKING STRENGTH FUERZA DE ROTURA	≥ 1471.7 N	≥ 700N	UNI EN ISO 10545-4
	CHEMICAL RESISTANCE RESISTENCIA A PRODUCTOS QUIMICOS	≥ UA	≥ GB	UNI EN ISO 10545-14
	STAIN RESISTANCE RESISTENCIA A LA MANCHAS	Class 3	≥ 3 GRADE	UNI EN ISO 10545-14
	ABRASION RESISTANCE (PEI) RESISTENCIA A LA ABRASION SUPERFICIAL (PEI)	-	1-5	UNI EN ISO 10545-6
	MOHS HARDNESS DUREZA SUPERFICIAL (ESCALA MOHS)	≥ 6	1-8	UNI EN ISO 10545-7
	SHADE VARIATION CLASS VARIACION DE TONALIDAD	V2	V1-V4	DIN 51094

PACKING INFORMATION
INFORMACION DE EMPAQUES

SIZE FORMATO	M2/BOX M2/CNT	PCS./BOX PZA./CAJA	BOX/PALLET CAJA/PALETA	M2/PALLET M2/PALETA	KG/BOX KG/CAJA	KG/PALLET KG/PALETA
40 x 40 cm	1.28	8	72	92.16	22	1580